



## SAFETY DATA SHEET CHEMOSIL 512

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME CHEMOSIL 512  
PRODUCT NO. 3016586  
APPLICATION For industrial and professional use only. Elastomer bonding agent.  
SUPPLIER LORD Germany GmbH  
Ottostrasse 28  
D-41836 Hückelhoven  
Germany  
TEL : +49 (0) 2433-5257-0  
FAX: + 49 (0) 2433-5257-18  
EuropeMSDS@lord.com  
EMERGENCY TELEPHONE +49 (0) 2433 5257-0 Only available during office hours.

### 2 HAZARDS IDENTIFICATION

Highly flammable. Causes burns. Vapours may cause drowsiness and dizziness.

CLASSIFICATION C;R34. F;R11. R67.

#### PHYSICAL AND CHEMICAL HAZARDS

Solvents contained in the product evaporate during processing and their vapours can form explosive/highly inflammable air/vapour mixtures.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

| Name                        | EC No.    | CAS-No.   | Content | Classification       |
|-----------------------------|-----------|-----------|---------|----------------------|
| 3-AMINOPROPYLTRIETHOXSILANE | 213-048-4 | 919-30-2  | 10-30%  | C;R34 Xn;R22         |
| BUTANONE                    | 201-159-0 | 78-93-3   | 60-100% | F;R11 Xi;R36 R66 R67 |
| XYLENE                      | 215-535-7 | 1330-20-7 | 1-5%    | R10 Xn;R20/21 Xi;R38 |

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### GENERAL INFORMATION

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention. NOTE! Keep affected person away from heat, sparks and flames! NOTE! Effects may be delayed. Keep affected person under observation.

#### INHALATION

Move the exposed person to fresh air at once. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

#### INGESTION

Immediately rinse mouth and drink plenty of water (200-300 ml). DO NOT induce vomiting. Get medical attention immediately. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

#### SKIN CONTACT

Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Immediately rinse with water for several minutes. Hold eyelids apart. Consult a physician for specific advice.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc. Carbon dioxide (CO<sub>2</sub>). Water fog.

## CHEMOSIL 512

### UNUSUAL FIRE & EXPLOSION HAZARDS

Risk of explosion in closed containers if pressure rises rapidly. Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back.

### SPECIFIC HAZARDS

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures. Fire or high temperatures create: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Refer to section 10 of this safety data sheet for more information on hazardous decomposition products.

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Collect with absorbent, non-combustible material into suitable containers.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Static electricity and formation of sparks must be prevented. Keep away from heat, sparks and open flame. Use explosion proof electric equipment. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Observe good industrial hygiene practices.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

### STORAGE CLASS

Flammable liquid storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Name     | Std | TWA - 8 hrs    |                  | STEL - 15 min  |                  | Notes |
|----------|-----|----------------|------------------|----------------|------------------|-------|
|          |     |                |                  |                |                  |       |
| BUTANONE | WEL | 200<br>ppm(Sk) | 600<br>mg/m3(Sk) | 300<br>ppm(Sk) | 899<br>mg/m3(Sk) |       |
| XYLENE   | WEL | 50 ppm(Sk)     | 220<br>mg/m3(Sk) | 100<br>ppm(Sk) | 441<br>mg/m3(Sk) |       |

WEL = Workplace Exposure Limit.

### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

### PROTECTIVE EQUIPMENT



### ENGINEERING MEASURES

Explosion-proof general and local exhaust ventilation.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit. In case of inadequate ventilation or when the product is heated, use suitable respiratory equipment with gas filter (type A2).

### HAND PROTECTION

Use protective gloves made of: Butyl rubber. Polyvinyl alcohol (PVA). Viton rubber (fluor rubber). The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

### EYE PROTECTION

Use approved safety glasses with side shields. If risk of splashing, wear safety goggles or face shield.

## CHEMOSIL 512

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

|                               |                             |                               |        |
|-------------------------------|-----------------------------|-------------------------------|--------|
| APPEARANCE                    | Liquid                      |                               |        |
| COLOUR                        | Clear Brown                 |                               |        |
| ODOUR                         | Aromatic. Organic solvents. |                               |        |
| SOLUBILITY                    | Insoluble in water          |                               |        |
| RELATIVE DENSITY              | 0.84 - 0.86 @ 20°C          | VISCOSITY                     | @ 25°C |
| FLASH POINT (°C)              | -6 CC (Closed cup).         | FLAMMABILITY LIMIT - LOWER(%) | 1.8    |
| FLAMMABILITY LIMIT - UPPER(%) | 11.5                        |                               |        |

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions.

### CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

### HAZARDOUS POLYMERISATION

Hazardous polymerisation will not occur under normal conditions.

### MATERIALS TO AVOID

None if used for intended purposes.

### HAZARDOUS DECOMPOSITION PRODUCTS

None under normal conditions. Fire or high temperatures create: Oxides of: Carbon.

## 11 TOXICOLOGICAL INFORMATION

### GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. The present product is a chemical preparation within the meaning of the REACH Regulation 1907/2006/EC. To avoid testing the product in animal experiments the evaluation is made based on toxicological data and content by weight of the individual ingredients according to 1999/45/EC or analogous evaluations of comparable products.

### INHALATION

Vapours may cause drowsiness and dizziness.

### INGESTION

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

### SKIN CONTACT

Causes burns.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

Do not empty into drains, soil or bodies of water.

### WATER HAZARD CLASSIFICATION

WGK 2 (VwVwS 17 May 1999 Annex 4)

## 13 DISPOSAL CONSIDERATIONS

### GENERAL INFORMATION

The valid EEC waste code numbers are not product-related but are largely source-related. The manufacturer is therefore unable to specify EEC waste codes for the articles or products used in the various sectors. These can be requested from the manufacturer. When handling waste, consideration should be made to the safety precautions applying to handling of the product.

### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

## CHEMOSIL 512

### 14 TRANSPORT INFORMATION



|                      |  |                         |                             |
|----------------------|--|-------------------------|-----------------------------|
| UK ROAD CLASS        | 3  |                         |                             |
| PROPER SHIPPING NAME | FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Methyl ethyl ketone, Amino propyl triethoxy silane) |                         |                             |
| UN NO. ROAD          | 2924   | UK ROAD PACK GR.        | II                          |
| ADR CLASS NO.        | 3  | ADR CLASS               | Class 3: Flammable liquids. |
| ADR PACK GROUP       | II   | TUNNEL RESTRICTION CODE | (D/E)                       |
| HAZARD No. (ADR)     | 338  | ADR LABEL NO.           | 3 & 8                       |
| HAZCHEM CODE         | •3WE   | CEFIC TEC(R) NO.        | 30GFC-II                    |
| RID CLASS NO.        | 3  | RID PACK GROUP          | II                          |
| UN NO. SEA           | 2924   | IMDG CLASS              | 3                           |
| IMDG PACK GR.        | II   | EMS                     | F-E, S-C                    |
| UN NO. AIR           | 2924   | AIR CLASS               | 3                           |
| AIR SUB CLASS        | 8  | AIR PACK GR.            | II                          |

### 15 REGULATORY INFORMATION

#### LABELLING



Corrosive



Highly Flammable

CONTAINS 3-AMINOPROPYLTRIEHOXSILANE

#### RISK PHRASES

|     |   |
|-----|---|
| R11 | Highly flammable.                           |
| R34 | Causes burns.                               |
| R67 | Vapours may cause drowsiness and dizziness. |

#### SAFETY PHRASES

|           |   |
|-----------|---|
| S7/9      | Keep container tightly closed and in a well-ventilated place.   |
| S16       | Keep away from sources of ignition - No smoking.  |
| S26       | In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.           |
| S36/37/39 | Wear suitable protective clothing, gloves and eye/face protection.                                      |
| S45       | In case of accident or if you feel unwell, seek medical advice immediately (show label where possible). |

#### EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

### 16 OTHER INFORMATION

#### INFORMATION SOURCES

Dangerous Properties of Industrial Materials Report, N.Sax et.al. Safety Data Sheets, Misc. manufacturers. GESTIS-database on hazardous substances ([www.dguv.de/bgia/gestis-database](http://www.dguv.de/bgia/gestis-database)).

#### ISSUED BY

EU Regulatory Compliance Specialist (Product Safety).

REVISION DATE 02/02/2010

## CHEMOSIL 512

REV. NO./REPL. SDS GENERATED 1

SDS NO. 13135

DATE 02.02.2010

### RISK PHRASES IN FULL

|        |   |
|--------|---|
| R10    | Flammable.  |
| R11    | Highly flammable.                                     |
| R20/21 | Harmful by inhalation and in contact with skin.       |
| R22    | Harmful if swallowed.                                 |
| R34    | Causes burns.   |
| R36    | Irritating to eyes.                                   |
| R38    | Irritating to skin.                                   |
| R66    | Repeated exposure may cause skin dryness or cracking. |
| R67    | Vapours may cause drowsiness and dizziness.           |

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.